

Data Sheet | Force Transducer Series K

Nominal Force
0.2 kN — 630 kN



Key Facts

- ▶ Applications: materials testing | component and structural testing | industrial quality and process control
- ▶ Compressive and tensile forces, static and dynamic
- ▶ Flat, robust design | low mass, high resonance frequency
- ▶ Accuracy class: 0.02 to 0.05 | high-precision measurement results over the entire measuring range
- ▶ Force introduction via flange or thread
- ▶ Fatigue and long-term stability | cycles: > 100 million cycles ^{*note amplitude}
- ▶ Standard variants with short delivery time or configurable variants for maximum flexibility

Options | Accessories

- ▶ Available as flange, threaded or flange and threaded version
- ▶ Optional second axial measuring circuit for redundancy
- ▶ Optional bending moment measuring circuits M_x, M_y
- ▶ Optional expanded temperature range
- ▶ Extensive electrical connection options
- ▶ Extensive mechanical accessories
- ▶ Tension Torsion combination with Series M torque transducer

Technical Data | 0.2 – 2.5 kN

Nominal force/compression/tension		$\pm F_{nom}$	kN	0.2	0.5	1	2.5	
Metrological Data	Accuracy class			0.02				
	Force measurement range		%	1 - 100				
	Linearity error	d_{lin}	%	0.02				
	Interpolation error	f_c	%	0.4				
	Hysteresis	h	%	0.02				
	Reversibility error	v	%	0.2				
	Repeatability (f.s.)		%	0.003				
	Creep		%	0.03				
	Temperature effect on characteristic value per 10 K	TK_C	%/10 K	0.04				
	Temperature effect on zero signal per 10 K	TK_0	%/10 K	0.025				
	Eccentricity effect		%/mm	0.015				
	Bending moment effect		%/N·m	0.075	0.03	0.015	0.006	
	Lateral force effect		%/(0.1· F_{nom})	0.02				
	Torque effect		%/(mm· F_{nom})	0.2				
	Characteristic value difference, tension/compression force	d_{ZD}	%	0.15				
	Electrical Data	Rated characteristic value	C_{nom}	mV/V	2			
		Characteristic value tolerance	d_c	%	0.2			
Zero signal deviation		$d_{S,0}$	%	0.5				
Input resistance		R_e	Ω	> 550				
Output resistance		R_a	Ω	> 400				
Insulation resistance		R_{is}	Ω	> 10^9				
Operating range of excitation voltage		$B_{U,G}$	V	5 - 20				
Protection (DIN EN 60529)				50 ¹⁾ ; 67 ²⁾				

Technical Data | 0.2 – 2.5 kN

Mechanical Data	Nominal force/compression/tension	$\pm F_{nom}$	kN	0.2	0.5	1	2.5
	Rated Displacement	s_{nom}	mm	0.05			
	Spring rigidity	c_{ax}	kN/mm	3.5	7	14	35
	Mass	m	kg	0.3		0.5	
	Proportionate moving mass	m_{mess}	kg	0.01		0.013	
	Fundamental resonant frequency	f_G	kHz	8			
	Permissible oscillation stress		%	± 80			
Limits	Force limit		%	±150			
	Breaking force		%	> 300			
	Lateral force limit		%	±100			
	Permissible eccentricity	e_G	mm	10			
	Bending moment limit	M_{bzul}	N·m	2.5	5	15	30
	Rated temperature range	$B_{T,nom}$	°C	10 - 60			
	Operating temperature range	$B_{T,G}$	°C	-40 - +120			

1) Connection pluggable

2) Permanent connection

Technical Data | 4 – 630 kN

Nominal force compression/tension		$\pm F_{nom}$	kN	4 5 6.3	10 20 25	40 50 63	100	150	160	200 250	400 500	630
Accuracy class				0.02						0.03	0.05	
Force measurement range		%	1 - 100									
Linearity error	d_{lin}	%	0.02						0.03			
Interpolation error	f_c	%	0.4									
Hysteresis	h	%	0.02						0.03	0.05	0.08	
Reversibility error	v	%	0.2									
Repeatability (f.s.)		%	0.003									
Creep		%	0.025									
Temperature effect on characteristic value per 10 K	TK_C	%/10 K	0.04									
Temperature effect on zero signal per 10 K	TK_0	%/10 K	0.025									
Eccentricity effect		%/mm	0.015									
Bending moment effect		%/N·m	< 0.003									
Lateral force effect		%/(0.1·F _{nom})	0.02									
Torque effect		%/(mm·F _{nom})	0.005									
Characteristic value difference, tension/compression force	d_{ZD}	%	0.07						0.1			
Rated characteristic value ³⁾	C_{nom}	mV/V	2			1; 2			1; 2		2	
Characteristic value tolerance	d_c	%	0.2									
Zero signal deviation	$d_{S,0}$	%	0.5									
Input resistance	R_e	Ω	1000	1100	1100	1200			1000	1100		
			-	-	-	-			-	-		
Output resistance	R_a	Ω	1200	1400	1200	1500			1200	1500		
			900	900	900	1000			800	900	1000	
Insulation resistance	R_{is}	Ω	-	-	-	-			-	-		
			1000	1200	1100	1200			1000	1100	1200	
Operating range of excitation voltage	$B_{U,G}$	V	5 - 20									
Protection (DIN EN 60529)			50 ¹⁾ ; 68 ²⁾									

Metrological Data

Electrical Data

Technical Data | 4 – 630 kN

		$\pm F_{nom}$	kN	4 5 6.3	10 20 25	40 50 63	100	150	160	200 250	400 500	630
Mechanical Data	Nominal force compression/tension											
	Rated Displacement ⁴⁾	s_{nom}	mm	0.093 0.08 0.086	0.071		0.12	0.15	0.16	0.19	0.21	0.32
	Spring rigidity ⁴⁾	c_{ax}	kN/mm	43 70 73	140 280 350	560 700 890	830	1000		1050 1300	1900 2400	2000
	Mass	m	kg	0.5	1	1.2	3.7			10.4	20	31
	Proportionate moving mass	m_{mess}	kg	0.12	0.22	0.35	0.8			2.4	4	5
	Fundamental resonant frequency ⁴⁾	f_G	kHz	3 3.5 4	4	6.8	5			3.7	4	3
	Permissible oscillation stress ³⁾		%	± 80								
	Force limit		%	150								
Breaking force		%	300									
Lateral force limit		%	100									
Permissible eccentricity	e_G	mm	10			15			20	25		
Bending moment limit	M_{bzul}	kN·m	0.25	0.4	1	3.5	5		10	20		
Rated temperature range	$B_{T,nom}$	°C	10 – 60									
Operating temperature range	$B_{T,G}$	°C	- 40 – +120									

1) Plug-in connection

2) Permanent connection


3) Rated characteristic value 1mV/V with permissible oscillation stress ± 100 % available on request.

4) Information for rated characteristic value 2mV/V; 1mV/V available on request.

Miscellaneous

Nominal force [kN] compression/tension	0.2 0.5 1 2.5	4 5 6,3	10 20 25	40 50 63	100	150	160	200 250	400 500	630
Series K transducer version: flange = F			✓	✓	✓	✓	✓	✓	✓	✓
Series K transducer version: thread = T	✓		✓	✓						
Series K transducer version: thread and flange = B		✓								
Measuring principle bending beam according to the principle of the symmetrical spoke	✓									
Measuring principle bending ring						✓				
Material spring body	0.2 kN - 0.5 kN: high strength aluminium alloy 1 kN - 630 kN: alloyed heat treated steel Other special steels on request									

Cable Connection | 0.2 – 630 kN



		Configurable variants Fixed cable connection with open cable ends	All standard variants Plug-in cable connection ¹⁾²⁾
		SMC: grey Ø 6.5 mm twisted in pairs 3 x 2 x 0.25 mm ² -35 °C to +90 °C	7-pole LEMO Series 1 Female: - Male:
		TMC: red Ø 7.2 mm twisted in pairs 3 x 2 x 0.25 mm ² -50 °C to +180 °C	
Connection		Wire colour	Pin
Supply voltage (+)	U _{in+}	SMC: blue TMC: white	3
Supply voltage (-)	U _{in-}	SMC: black TMC: brown	2
Measurement signal (+)	U _{out+}	SMC: white TMC: grey	1
Measurement signal (-)	U _{out-}	SMC: red TMC: pink	4
Sense (+)	Sense+	SMC: green TMC: green	5
Sense (-)	Sense-	SMC: grey TMC: yellow	6
Shielding		SMC: yellow TMC: black	Housing

1) View too weldingside


2) Female LEMO S.A. Typ: EGG.1B.307.CLL; Male: FGG.1B.307.CLA.D72

► Pluggable cable connection

All standard variants of the series K are equipped with a pluggable LEMO socket. Suitable measuring cables S-CAB / C-CAB are available as accessories.



► Plug-in cable connection with shielded measuring cable type SMC (S-CAB-L-5M-F)




► Fixed measuring cable

All configurable variants of the series K are optionally available with fixed measuring cables, e.g. with 5 / 10 m shielded standard measuring cable type SMC or 5 m high / low temperature measuring cables and open cable ends or various connectors for strain gauge measuring amplifier connections.



► Fixed shielded measuring cable type SMC with open cable ends



► Fixed shielded high/low temperature measuring cable type TMC with open cable ends




► Fixed shielded measuring cable type SMC with connector



► Fixed shielded high/low temperature measuring cable type TMC with connector

Double Bridge | 4 – 630 kN

► For the double measuring bridge (available as configurable variant), the technical data apply equally to both measuring circuits.



► **Standard force transducer series K**
Single bridge | 1 x LEMO push-pull connection socket (female) | flange version



► **Configurable force transducer series K**
Double bridge | 2 x LEMO push-pull connection sockets (female) | flange version

Bending Moment Measuring Circuits | 4 – 630 kN

► The bending moment measuring circuits (available as configurable variant) Mx and My can be used advantageously with the use of a multi-channel measuring amplifier to control the force application.




► **Configurable force transducer series K**
Single bridge | | bending moment measuring circuits Mx, My | 3 x LEMO push-pull connection sockets (female) | flange version

Nominal force	F_{nom}	kN	4 - 630 (2mV/V)	100 - 630 (1 mV/V)
Rated bending moment	Mb_{nom}	N·m	$F_{nom} \cdot 8 \text{ mm}$	$F_{nom} \cdot 12 \text{ mm}$
Reproducibility		%	0.01	
Temperature effect on characteristic value per 10 K	TK_C	%/10 K	0.2	
Temperature effect on zero signal per 10 K	TK_0	%/10 K	0.2	
Rated characteristic value	C_{nom}	mV/V	ca. 0.3	
Input resistance	R_e	Ω	400	
Operating range of excitation voltage	$B_{U, G}$	V	5 - 12	

Dimensions | Threaded Version | 0.2 – 2.5 kN


- ▶ Force transducer Series K design: thread
- ▶ Transducer design: 0.2 kN - 2.5 kN



Nominal force compression/tension	$\pm F_{nom}$	kN	0.2	0.5	1	2.5
Bore	$\varnothing B_1$	mm		5.5		
Diameter	$\varnothing D_1$	mm		77		
Diameter	$\varnothing D_2$	mm		68-0.1		
Diameter	$\varnothing D_3$	mm		15		
Diameter	$\varnothing D_4$	mm		12+0.1		
Pitch circle diameter	$\varnothing P_1$	mm		67±0.1		
Thread	T_1			M8		
Height	H_1	mm		24		
Height	H_2	mm		12.5		
Height	H_3	mm		2		
Height	H_4	mm		1		
Height	H_5	mm		2		
Angle	a_1			60°		
Angle	a_2			30°		

Dimensions | Flange & Threaded Version | 4 – 6.3 kN


- ▶ Force transducer Series K design: flange and thread
- ▶ Transducer design: 4 kN - 6.3 kN



Nominal force compression/tension	$\pm F_{nom}$	kN	4 5 6.3
Bore	$\varnothing B_1$	mm	5.3
Bore	$\varnothing B_2$	mm	20 \pm 0.1
Diameter	$\varnothing D_1$	mm	77-0.1
Diameter	$\varnothing D_2$	mm	68-0.05
Diameter	$\varnothing D_3$	mm	27.3
Diameter	$\varnothing D_4$	mm	12.7 \pm 0.05
Pitch circle diameter	$\varnothing P_1$	mm	67 \pm 0.1
Pitch circle diameter	$\varnothing P_2$	mm	20 \pm 0.1
Thread	T_1		M10 x 1
Height	H_1	mm	26-0.1
Height	H_2	mm	13
Height	H_3	mm	2
Height	H_4	mm	2
Height	H_5	mm	16
Angle	a_1		6 x 60°
Angle	a_2		30°

Dimensions | Threaded Version | 10 – 63 kN


- ▶ Force transducer Series K design: thread
- ▶ Transducer design: 10 kN - 63 kN



Nominal force compression/tension	$\pm F_{nom}$	kN	10 20	25	40 50 63
Bore	$\varnothing B_1$	mm	6.6		
Diameter	$\varnothing D_1$	mm	95 ^{-0.1}		101 ^{-0.1}
Diameter	$\varnothing D_2$	mm	81 ^{-0.1}		87,5 ^{-0.1}
Diameter	$\varnothing D_3$	mm	40 ^{-0.1}		38,6 ^{-0.1}
Pitch circle diameter	$\varnothing P_1$	mm	80 \pm 0.1		86 \pm 0.1
Thread	T_1		M20 x 1.5		
Height	H_1	mm	31 ^{-0.1}		
Height	H_2	mm	18		
Height	H_3	mm	1	1.5	
Height	H_4	mm	1		
Angle	a_1		8 x 45°		
Angle	a_2		22.5°		

Dimension | Flange Version | 10 – 160 kN


- ▶ Force transducer Series K design: flange
- ▶ Transducer design: 10 kN - 160 kN



Nominal force compression/tension	$\pm F_{nom}$	kN	10 20	25	40 50 63	100 150 160
Bore	$\varnothing B_1$	mm	6.6			11
Bore	$\varnothing B_2$	mm	6.6			11
Diameter	$\varnothing D_1$	mm	95-0.1		101-0.1	148-0.1
Diameter	$\varnothing D_2$	mm	81-0.1		87,5-0.1	131,4-0.1
Diameter	$\varnothing D_3$	mm	40-0.1		38,6-0.1	63
Diameter	$\varnothing D_4$	mm	8 \pm 0			10 \pm 0,1
Pitch circle diameter	$\varnothing P_1$	mm	80 \pm 0.1		86 \pm 0.1	130 \pm 0.1
Pitch circle diameter	$\varnothing P_2$	mm	30 \pm 0.1			45 \pm 0.1
Height	H_1	mm	31-0.1			49-0.1
Height	H_2	mm	18			25
Height	H_3	mm	1		1.5	0.5
Height	H_4	mm	1			
Angle	a_1		8 x 45°			
Angle	a_2		22.5°			

Dimension | Flange Version | 200 – 630 kN

- ▶ Force transducer Series K design: flange
- ▶ Transducer design: 200 kN - 630 kN



Nominal force compression/tension	$\pm F_{nom}$	kN	200 250	400 500	630
Bore	$\varnothing B_1$	mm	17	22	26
Bore	$\varnothing B_2$	mm	17	22	26
Diameter	$\varnothing D_1$	mm	219 \pm 0.1	270 \pm 0.1	312 \pm 0.2
Diameter	$\varnothing D_2$	mm	171,05 \pm 0.1	203 \pm 0.1	226 \pm 0.1
Diameter	$\varnothing D_3$	mm	97 \pm 0.1	128 \pm 0.1	151 \pm 0.1
Diameter	$\varnothing D_4$	mm	10 \pm 0.1		
Pitch circle diameter	$\varnothing P_1$	mm	194 \pm 0.1	235 \pm 0.1	267 \pm 0.1
Pitch circle diameter	$\varnothing P_2$	mm	71 \pm 0.1	95 \pm 0.1	112 \pm 0.1
Height	H_1	mm	60 \pm 0.1	80 \pm 0.1	90 \pm 0.1
Height	H_2	mm	32	40	45
Height	H_3	mm	1		
Angle	a_1		8 x 45°		
Angle	a_2		22.5°		

Order Numbers | Standard Variants

► Force transducer Series K | standard variants available at short notice

Nominal force	Description	Order number
200 N	Standard force transducer series K 0.2 kN threaded version	S-K-K200-T
500 N	Standard force transducer series K 0.5 kN threaded version	S-K-K500-T
1 kN	Standard force transducer series K 1 kN threaded version	S-K-1K00-T
2.5 kN	Standard force transducer series K 2.5 kN threaded version	S-K-2K50-T
5 kN	Standard force transducer series K 5 kN threaded and flanged version	S-K-5K00-B
10 kN	Standard force transducer series K 10 kN flange version	S-K-10K0-F
10 kN	Standard force transducer series K 10 kN threaded version	S-K-10K0-T
20 kN	Standard force transducer series K 20 kN flange version	S-K-20K0-F
20 kN	Standard force transducer series K 20 kN threaded version	S-K-20K0-T
25 kN	Standard force transducer series K 25 kN flange version	S-K-25K0-F
25 kN	Standard force transducer series K 25 kN threaded version	S-K-25K0-T
40 kN	Standard force transducer series K 40 kN flange version	S-K-40K0-F
50 kN	Standard force transducer series K 50 kN flange version	S-K-50K0-F
50 kN	Standard force transducer series K 50 kN threaded version	S-K-50K0-T
63 kN	Standard force transducer series K 63 kN flange version	S-K-63K0-F
63 kN	Standard force transducer series K 63 kN threaded version	S-K-63K0-T
100 kN	Standard force transducer series K 100 kN flange version	S-K-100K-F
150 kN	Standard force transducer series K 150 kN flange version	S-K-150K-F
200 kN	Standard force transducer series K 200 kN flange version	S-K-200K-F
250 kN	Standard force transducer series K 250 kN flange version	S-K-250K-F
500 kN	Standard force transducer series K 500 kN flange version	S-K-500K-F
630 kN	Standard force transducer series K 630 kN flange version	S-K-630K-F

Note: all standard versions always (1) without attachments (2) no plug protection (3) 2 mV/V (4) single measuring bridge (5) standard temperature range (6) 1xLEM O connection socket 7-pin push-pull | no measuring cables included

Order Numbers | Configurable Variants

► Force transducer Series K | configurable variants

Item	Code	Description
Force Transducer Series K	C-K	Configurable force transducer series K
Nominal Force	K200	200 N
	K500	500 N
	1K00	1 kN
	2K50	2.5 kN
	4K00	4 kN
	5K00	5 kN
	6K30	6.3 kN
	10K0	10 kN
	20K0	20 kN
	25K0	25 kN
	40K0	40 kN
	50K0	50 kN
	63K0	63 kN
	100K	100 kN
	150K	150 kN
	160K	160 kN
200K	200 kN	
250K	250 kN	
400K	400 kN	
500K	500 kN	
630K	630 kN	
Mechanical design	F	Flange
	T	Thread
	B	Flange and thread
Mounting adapter	N	No mounting parts
	Y	With mounting parts
Plug protection	N	No plug protection
	Y	With plug protection
Nominal sensitivity	2	2 mV/V
	1	1 mV/V
Single or double measuring bridge	SB	Single bridge
	DB	Double bridge
Bending moment measuring circuits Mx, My	NO	No bending moment measuring circuits Mx, My
	BM	Bending moment measuring circuits Mx, My
Temperature range	S	Standard temp. range +10°C - +60°C
	E	Extended temp. range +10°C - ≤+120°C temperature adjustment
	L	Low and extended temp. range -40°C - ≤+120°C temp. adjustment low temp. protective measures
	H	High temp. range +10°C - +180°C temp. adjustment high temp. protective measures
Electrical transducer connection (for all selected measuring circuits)	B	High and low temp. range -40°C - +180°C temp. adjustment high and low temp. protective measures
	P	LEMO connection sockets(s) 7-pole push-pull on all measuring circuits
Cable connection type (for all selected measuring circuits)	A	1 x 5 m fixed standard measuring cable type SMC on all measuring circuits
	B	1 x 10 m fixed standard measuring cable type SMC on all measuring circuits
	S	1 x 5 m fixed high/low temperature measuring cable type TMC on all measuring
	P	LEMO connection sockets(s) selected no fixed measuring cable(s)
	F	Free cable ends
	A	D-Sub 9-pole plug
B	D-Sub 15-pole plug	
C	MS 7-pole plug	
M	M12 8-pole plug (for in-line amplifier series ILA)	

Order-Example

C	- K	- 630K	- F	- N	- N	- 2	- DB	- NO	- S	- A	- F
		630 kN	flange	no mounting parts	no plug protection	2 mV/V	double bridge	no bending moment Mx, My	standard temperatur	5 m fixed cable type SMC	free ends

Order Numbers | Configurable Variants

Item	Description
Mechanical design	The series K force transducer has different mechanical interfaces depending on the nominal load. F = Flange version nominal load: 10 - 630 kN T = Threaded version nominal load: 0.2 - 2.5 kN and 10 - 63 kN B = Flange & threaded version nominal load: 4 - 6.3 kN
Mounting adapter	Depending on the nominal load, the force transducer series K can be equipped with additional attachments. The attachments are all pre-assembled at the factory. - Nominal load: 0.2 - 2.5 kN with base plate M8 screwed - Nominal load: 4 - 6.3 with base plate M10x1 screwed - Nominal load: 10 - 63 kN with base plate M20x1.5 screwed - Nominal load: 100 - 160 kN with base plate and thread adapter M30x2 screwed - Nominal load: 200 - 250 kN with base plate and threaded adapter M42x3 screwed - Nominal load: 400 - 500 kN with base plate and threaded adapter M56x4 screwed - Nominal load: 630 kN with base plate and threaded adapter M56x4 screwed
Plug protection	In special cases it may be necessary to additionally equip the electrical connections on the force transducer series K with a protective profile around the plug connection. Dimensions depending on nominal load.
Nominal sensitivity	The series K force transducer is specified for a permissible oscillation stress $\pm 80\%$ (@2 mV/V). For the nominal forces 100 kN - 500 kN the option nominal value 1 mV/V can be selected. This allows a permissible oscillation stress of $\pm 100\%$ (@1 mV/V) to be achieved for these ranges.
Single or double measuring bridge 4 - 630 kN	For redundancy reasons, it is necessary, for example in safety-relevant applications, to check the safety-relevant integrity of the measuring signal by means of a second measuring bridge (functional redundancy in the same force transducer). Via two separate measuring amplifier channels, two series K force transducers output signals are processed and evaluated independently of each other. This makes it possible to connect two measuring amplifiers with different characteristics (DC / CF). The second redundant measuring circuit is characterised by no crosstalk between the channels at different carrier frequencies. The selection of a double measuring bridge affects the number of connection sockets and measuring cables (if selected).
Bending moment measuring circuits Mx, My 4 - 630 kN	The series K force transducer can be optionally equipped with bending moment measuring circuits. The additional bending moment measuring circuits can be measured to control the horizontal bending moments Mx and My and can be provided as separate channels. The selection of bending moment measuring circuits affects the number of connection sockets and measuring cables (if selected).
Temperature range	The selection of the temperature range has an effect on the feature electrical transducer connection / measuring cables, additional temperature compensation and additional protective measures for high and / or low temperature ranges. S = For the standard temperature range +10°C - +60°C shielded measuring cables type SMC are used. E = For the extended temperature range +10°C - ? +120°C shielded high/low temperature measuring cables type TMC are used additional temperature compensation L = For the low and extended temperature range -40°C - ? +120°C shielded high/low temperature measuring cables type TMC are used additional temperature compensation additional protective measures for use in the low temperature range H = For the high temperature range +10° - +180°C shielded high/low temperature measuring cables type TMC are used additional temperature compensation additional protective measures for use in the high temperature range B = For the high and low temperature range -40° - +180°C shielded high/low temperature measuring cables type TMC are used additional temperature compensation additional protective measures for use in the high and low temperature range Note: temperature compensation ensures that the series K force transducer fulfills the metrological characteristics over the selected temperature range.
Electrical transducer connection	The series K force transducer can be configured with fixed push-pull connection plugs (female) or fixed cables (type SMC or TMC) in different lengths. P = LEMO connection socket(s) 7-pole push-pull A = 5 m fixed standard measuring cable type SMC B = 10 m fixed standard measuring cable type SMC S = 5 m fixed high/low temperature measuring cable type TMC Notes: The number of connection plugs and measuring cables results from the number of selected measuring bridges. The type of measuring cable depends on the selected temperature range.
Cable connection type	If the series K force transducer is configured with fixed measuring cables, different connector types for strain-gauge measuring amplifiers can be selected in addition to open cable ends. The assembly of the selected connectors is carried out by GTM. The force transducer can be connected directly to a measuring amplifier. P = LEMO push-pull connection socket(s) no fixed measuring cables F = free cable ends on all configured measuring circuits A = D-Sub 9-pin on all configured measuring circuits B = D-Sub 15-pin on all configured measuring circuits C = MS 7-pole on all configured measuring circuits M = M12 8-pole on all configured measuring circuits

Order Numbers | Accessories

Description	Order number
Measuring cable	
Standard measuring cable grey 5 m shielded and twisted in pairs cable sheath Ø 6.5 mm 6-wire technology transducer connection: straight plug (male) type LEMO 7-pole push-pull cable end amplifier: open	S-CAB-SMC-L-5M-F
Standard measuring cable grey 5 m shielded and twisted in pairs cable sheath Ø 6.5 mm 6-wire technology transducer connection for series DR force and acceleration connection: straight bayonet plug (female) 6-pole cable end amplifier: open	S-CAB-SMC-B-5M-F
Double-shielded measuring cable yellow 5 m double shielded and twisted in pairs cable sheath Ø 6.5 mm 6-wire technology transducer connection: straight plug (male) type LEMO 7-pole push-pull (male) cable end amplifier: open	S-CAB-DMC-L-5M-F
Temperature-resistant measuring cable red 5 m shielded and twisted in pairs cable sheath Ø 7.2 mm 6-wire technology transducer connection: straight plug (male) type LEMO 7-pole push-pull (male) cable end amplifier: open	S-CAB-TMC-L-5M-F
High flexible measuring cable black 5 m double shielded and twisted in pairs cable sheath Ø 2.9 mm 6-wire technology transducer connection: straight plug (male) type LEMO 7-pole push-pull (male) cable end amplifier: open	S-CAB-FMC-L-5M-F
Configurable measuring cable type SMC, DMC, TMC, FMC in different lengths with different connectors	C-CAB-...
Series K Base plate (1 piece)	
Series K 0.2 - 0.5 kN base plate	S-MA-K-BP-00
Series K 1 - 2.5 kN base plate	S-MA-K-BP-01
Series K 4 - 6.3 kN base plate	S-MA-K-BP-02
Series K 10 - 25 kN base plate	S-MA-K-BP-03
Series K 40 - 63 kN base plate	S-MA-K-BP-04
Series K 100 - 160 kN base plate	S-MA-K-BP-05
Series K 200 - 250 kN base plate	S-MA-K-BP-06
Series K 400 - 500 kN base plate	S-MA-K-BP-07
Series K 630 kN base plate	S-MA-K-BP-08
<i>Note: 0.2 - 0.5 kN Material: aluminium</i>	
Series K bolts outer hole circle (1 set)	
Series K 0.2 - 0.5 kN bolts set outer hole circle	S-MA-K-BO-00
Series K 1 - 2.5 kN bolts set outer hole circle	S-MA-K-BO-01
Series K 4 - 6.3 kN bolts set outer hole circle	S-MA-K-BO-02
Series K 10 - 63 kN bolts set outer hole circle	S-MA-K-BO-03
Series K 100 - 160 kN bolts set outer hole circle	S-MA-K-BO-04
Series K 200 - 250 kN bolts set outer hole circle	S-MA-K-BO-05
Series K 400 - 500 kN bolts set outer hole circle	S-MA-K-BO-06
Series K 630 kN bolts set outer hole circle	S-MA-K-BO-07
<i>Note: 1 set for mounting the foot plate over outer hole circle</i>	

Order Numbers | Accessories

Description	Order number
Series K load button threaded version (1 piece)	
Series K 0.2 - 2.5 kN load button threaded version	S-MA-K-LB-T-00
Series K 4 - 6.3 kN load button threaded version	S-MA-K-LB-T-01
Series K 10 - 63 kN load button threaded version	S-MA-K-LB-T-02
Series K 100 - 160 kN load button threaded version	S-MA-K-LB-T-03
Series K 200 - 250 kN load button threaded version	S-MA-K-LB-T-04
Series K 400 - 630 kN load button threaded version	S-MA-K-LB-T-05
Series K load button flange version (1 piece)	
Series K 4 - 6.3 kN load button flange version	S-MA-K-LB-F-00
Series K 10 - 63 kN load button flange version	S-MA-K-LB-F-01
Series K 100 - 160 kN load button flange version	S-MA-K-LB-F-02
Series K 200 - 250 kN load button flange version	S-MA-K-LB-F-03
Series K 400 - 500 kN load button flange version	S-MA-K-LB-F-04
Series K 630 kN load button flange version	S-MA-K-LB-F-05
Series K flange tensile force introduction (1 piece)	
Series K 4 - 6.3 kN flange tensile force introduction	S-MA-K-F-F-00
Series K 10 - 63 kN flange tensile force introduction	S-MA-K-F-F-01
Series K 100 - 160 kN flange tensile force introduction	S-MA-K-F-F-02
Series K 200 - 250 kN flange tensile force introduction	S-MA-K-F-F-03
Series K 400 - 500 kN flange tensile force introduction	S-MA-K-F-F-04
Series K 630 kN flange tensile force introduction	S-MA-K-F-F-05
Series K bolts inner hole circle (1 set)	
Series K 4 - 6.3 kN bolts set inner bolt circle	S-MA-K-BI-00
Series K 10 - 63 kN bolts set inner hole circle	S-MA-K-BI-01
Series K 100 - 160 kN bolts set inner hole circle	S-MA-K-BI-02
Series K 200 - 250 kN bolts set inner hole circle	S-MA-K-BI-03
Series K 400 - 500 kN bolts set inner hole circle	S-MA-K-BI-04
Series K 630 kN bolts set inner hole circle	S-MA-K-BI-05
<i>Note: 1 set for mounting the tensile force introduction via inner hole circle</i>	
Series K tension bolts (1 set)	
Series K 4 - 6.3 kN tension bolts	S-MA-K-TB-00
Series K 10 - 63 kN tension bolts	S-MA-K-TB-01
Series K 100 - 160 kN tension bolts	S-MA-K-TB-02
Series K 200 - 250 kN tension bolts	S-MA-K-TB-03
Series K 400 - 500 kN tension bolts	S-MA-K-TB-04
Series K 630 kN tension bolts	S-MA-K-TB-05
<i>Note: expansion screws are recommended for dynamic use</i>	

Order Numbers | Accessories

Description	Order number
Series K thrust piece (1 piece)	
Series K 0.2 - 2.5 thrust piece	S-MA-K-TP-00
Series K 4 - 6.3 thrust piece	S-MA-K-TP-01
Series K 10 - 25 thrust piece	S-MA-K-TP-02
Series K 40 - 63 thrust piece	S-MA-K-TP-03
Series K 100 - 160 thrust piece	S-MA-K-TP-04
Series K 200 - 250 thrust piece	S-MA-K-TP-05
Series K 400 - 500 thrust piece	S-MA-K-TP-06
Series K 630 thrust piece	S-MA-K-TP-07
Series K threaded adapter flange (1 piece)	
Series K 10 - 63 kN threaded adapter flange	S-MA-K-TAF-00
Series K 100 - 160 kN threaded adapter flange	S-MA-K-TAF-01
Series K 200 - 250 kN Threaded adapter flange	S-MA-K-TAF-02
Series K 400 - 500 kN Threaded adapter flange	S-MA-K-TAF-03
Series K 630 kN Threaded adapter flange	S-MA-K-TAF-04
Series K tension Adapter (1 piece)	
Series K 4 - 6.3 kN tension adapter	S-MA-K-TA-00
Series K 10 - 63 kN tension adapter	S-MA-K-TA-01
Series K 100 - 150 kN tension adapter	S-MA-K-TA-02
Series K 200 - 250 kN tension adapter	S-MA-K-TA-03
Series K 400 - 500 kN tension adapter	S-MA-K-TA-04
Series K 630 kN tension adapter	S-MA-K-TA-05
Series K tension rod (1 piece)	
Series K 0.2 - 2.5 kN tension rod	S-MA-K-TR-00
Series K 4 - 6.3 kN tension rod	S-MA-K-TR-01
Series K 10 - 63 kN tension rod	S-MA-K-TR-02
Series K 100 - 150 kN tension rod	S-MA-K-TR-03
Series K 160 kN tension rod	S-MA-K-TR-04
Series K 200 kN tension rod	S-MA-K-TR-05
Series K 250 kN tension rod	S-MA-K-TR-06
Series K 400 - 500 kN tension rod	S-MA-K-TR-07
Series K 630 kN tension rod	S-MA-K-TR-08
Series K spherical shell / nut (1 pair)	
Series K 0.2 - 40 kN spherical shell / nut	S-MA-K-SWN-00
Series K 50 - 63 kN spherical shell / nut	S-MA-K-SWN-01
Series K 100 - 150 kN spherical shell / nut	S-MA-K-SWN-02
Series K 160 - 200 kN spherical shell / nut	S-MA-K-SWN-03
Series K 250 - 400 kN spherical shell / nut	S-MA-K-SWN-04
Series K 500 - 600 kN spherical shell / nut	S-MA-K-SWN-05
Series K 630 kN spherical shell / nut	S-MA-K-SWN-06

Subject to change without notice. All information describes our products in general terms. They do not represent agreed quality in the sense of § 434 Para. 1 of the BGB (German Civil Code). Illustrations may differ from originals.



GTM Testing and Metrology GmbH
 Philipp-Reis-Straße 4-6, 64404 Bickenbach, Germany
www.gtm-gmbh.com
contact@gtm-gmbh.com
 Phone +49(0)6257-9720-0
 Fax +49(0)6257-9720-77